

Weatherproof

Recessed Mounted Downlight IP:65

Features:-

- ❖ High Quality Die-casting Aluminum, and PMMA Diffuser, a sleek design with superior thermal management.
- ❖ Epistar SMD LED Chip
- ❖ Silicone gasket to prevent moisture ingress.
- ❖ Wide Beam Angel 100°
- ❖ PF>0.90
- ❖ IP65 protect class with PG7 connector.



Product Code	Input Voltage	Wattage	Luminous Flux (lm) ±5%	Color Temperature CCT	Dimension	Cutout	Working Temperature
DLWD / 10W	220-240V /AC	10W	1000 lm	2700K-6000K	D95*H51mm	Φ80~85mm	-30°~ 40°
DLWD / 15W	220-240V /AC	15W	1500 lm	2700K-6000K	D115*H55mm	Φ90~95mm	-30°~ 40°
DLWD / 20W	220-240V /AC	20W	2000 lm	2700K-6000K	D155*H67mm	Φ115~140mm	-30°~ 40°
DLWD / 25W	220-240V /AC	25W	2500 lm	2700K-6000K	D195*H60mm	Φ160~170mm	-30°~ 40°
DLWD / 30W	220-240V /AC	30W	2500 lm	2700K-6000K	D235*H65mm	Φ200~210mm	-30°~ 40°
DLWD / 35W	220-240V /AC	35W	2500 lm	2700K-6000K	D235*H65mm	Φ200~210mm	-30°~ 40°