

CONCAVE-II

Anti-glare Recessed Mounted Downlight

Trimless LED Downlight

Britlite Concave-II Trimless Led Downlight creates a seamless lighting effect. They blend into the ceiling allowing a super bright lighting ambience with the most minimalist of appearances.



Application:

- Villa, Lobbies, Corridors, Malls
- Hotels, Restaurants, Hospitals
- Residential Lighting



CONCAVE-II

Anti-glare Recessed Mounted Downlight

Information:

Features:

- LED Inside with Anti-glare rings UGR<16
- Various colors of reflectors optional for different application
- SDCM=3
- Extremely long lifetime
- Energy savings
- Excellent light quality
- No UV or IR radiation
- Environmentally-friendly: no mercury
- Medium useful life > 50,000 hours (L80B50) at ambient temperature of 25 °C

Specification:

- Power supply : Lifud or Philips
- Lighting Source: Original Philips (90Ra+) CREE (90Ra+)
- Housing material: aluminum.
- Housing color: White Black
- Working environment temperature: -20°C ~ +45°C
- Lamp Certificates: CE ROHS



Product Code	Electrical parameters			Optical parameters				Physical parameter	
	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(o)	CCT (K)	CRI	Size (mm)	Cutout (mm)
BL-DLH-WC-05	AC220-240V	5W	PHILIPS/CREE	100LM/W	15°/24°/38°	2700K 3000K 4000K 5000K	80+/90 +	Ø 55*H70	Ø55mm
BL-DLH-WC-07	AC220-240V	7W	PHILIPS/CREE	100LM/W	15°/24°/38°	2700K 3000K 4000K 5000K	80+/90 +	Ø 75*H76	Ø75mm
BL-DLH-WC-12	AC220-240V	12W	PHILIPS/CREE	100LM/W	15°/24°/38°	2700K 3000K 4000K 5000K	80+/90 +	Ø 75*H83	Ø75mm
BL-DLH-WC-15	AC220-240V	15W	PHILIPS/CREE	100LM/W	15°/24°/38°	2700K 3000K 4000K 5000K	80+/90 +	Ø 75*H100	Ø75mm
BL-DLH-WC-20	AC220-240V	20W	PHILIPS/CREE	100LM/W	15°/24°/38°	2700K 3000K 4000K 5000K	80+/90 +	Ø 95*H107	Ø95mm
BL-DLH-WC-25	AC220-240V	25W	PHILIPS/CREE	100LM/W	15°/24°/38°	2700K 3000K 4000K 5000K	80+/90 +	Ø 95*H107	Ø95mm