CUBE-ER SURFACE DOWNLIGHT

BRITLITE CUBE-ER Series, this series of LED surface mounted ceiling light is a commendable choice for commercial and residential places, like home, shop, hotel, restaurant and so on.

It adopts aluminum profile providing excellent thermal dissipation. Secondly, the driver can be fixed into the light body, which is more convenient for customers to save space and to install them.



Application:

- Shopping malls, jewelry shops and fashion stores.
- Art gallery, furniture, museum and showroom lighting.
- Gym, hotel, hospital and stage lighting.
- Food Lighting (Meat Fruit Vegetable Bread etc.)



















CUBE-ER SURFACE DOWNLIGHT

Features:

• Lighting Source: CREE COB LED

• CRI: 80+

• Dimming methods: Non dimmable or Triac Leading edge and trailing edge.

No need cutout, surface mount install or hanging install.

• Strongly lights up an object from far or high distance.

• Unique and compact design with perfect thermal management.

Specifications:

• Power supply : Lifud Driver

Power factor: >0.90

Housing material: Aluminum.

Housing color: White

Working environment temperature: -20°C ~ + 45°C

Lamp Certificates: CE ROSH SAA

Driver Certificates: TUV CB UL CE ROSH SAA





Product Code	Electrical Parameters			Optical Parameters			
	Input voltage(V)	Power (w)	LED Chip	Luminous flux (Im) (±5%)	Beam angle(o)	сст (к)	Size (mm)
Cube-ER	AC220-240V	10W	CREE	95LM/W	50°	2700K 5000K	D90 H90mm
Cube-ER	AC220-240V	20W	CREE	95LM/W	50°	2700K 5000K	D110 H120mm
Cube-ER	AC220-240V	30W	CREE	95LM/W	50°	2700K 5000K	D130 H135mm
Cube-ER	AC220-240V	40W	CREE	95LM/W	50°	2700K 5000K	D160 H165mm

CUBE-ER SURFACE DOWNLIGHT

Photo-Metric:

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM





Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



