

CUBE-IR SURFACE DOWNLIGHT

Description:

Britlite LED Cube-IR Downlight is a new generation product of lower energy consumption. It adopts high brightness high quality LED with low –voltage, & long lifespan reliability. Constructed from a die-cast and extruded aluminium body housing which is elegant and stylish to perfectly suit the aesthetics of your project, with no flickering, no glaring, free of lead, mercury and other harmful substances.

Britlite Cube-IR Series, this series of LED surface mounted ceiling light is a commendable choice for commercial and residential areas.



Application:

- Villa, Lobbies, Corridors
- Hotel Lighting Restaurant
- Residential Lighting



golden



silver



black



White

CUBE-IR SURFACE DOWNLIGHT

Features:

- LED Inside with Anti-glare rings UGR<13
- 5 colors of reflectors optional for different application
- SDCM=3
- Long lifetime
- Energy savings
- Maintenance savings
- instant light-up
- Excellent light quality
- No UV or IR radiation
- Environmentally-friendly: no mercury
- lifespan: > 50,000 hours (L80B50) at ambient temperature of 25° C



Specification:

- Power supply : Eaglerise /Osram
- Lighting Source: Bridgelux
- Housing material: Aluminum.
- Housing color: White Black
- Working environment temperature: -20°C ~+45°C
- Lamp Certificates: CE ROHS



Product Code	Electrical parameters			Optical parameters				Physical parameter	
	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(o)	CCT (K)	CRI	Size (mm)	Ring color
DLO-WE-07	AC220-240V	7W	Bridgelux	100LM/W	15/30/45°	2700K 3000K 4000K 5000K	90+	L55*W55*H120	Silver White Black Goden / Rose goden
DLO-WE-10	AC220-240V	10W	Bridgelux	100LM/W	15/30/45°	2700K 3000K 4000K 5000K	90+	L75*W75*H95	Silver White Black Goden / Rose goden
DLO-WE-15	AC220-240V	15W	Bridgelux	100LM/W	15/30/45°	2700K 3000K 4000K 5000K	90+	L75*W75*H130	Silver White Black Goden / Rose goden
DLO-WE-20	AC220-240V	20W	Bridgelux	100LM/W	15/30/45°	2700K 3000K 4000K 5000K	90+	L95*W95*H150	Silver White Black Goden / Rose goden
DLO-WE-25	AC220-240V	25W	Bridgelux	100LM/W	15/30/45°	2700K 3000K 4000K 5000K	90+	L115*W115*H110	Silver White Black Goden / Rose goden
DLO-WE-28	AC220-240V	28W	Bridgelux	100LM/W	15/30/45°	2700K 3000K 4000K 5000K	90+	L115*W115*H160	Silver White Black Goden / Rose goden