

CYLINDER

Surface Mounted Round Shape

Britlite LED Cylinder COB Down light is a new generation green product of lower energy consumption.

It adopts high brightness high quality LED as luminous body with low -voltage constant current driver, low power consumption, long lifespan, reliability Aluminum housing which is elegant and stylish, Built-in large area of heat dissipation Aluminum plate ensures stable working of LED, and controls light attenuation effectively, no flickering, no glaring. Free of lead, mercury and other harmful substances. IP Grade 44



Product Code	Input Voltage	LED	Wattage	Luminous Flux (lm) ±5%	Color Temperature CCT	Dimension	Life Span	Working Temperature
DLO-10-IR	220-240V /AC	CREE COB	10W	900 lm	2700K-5000K	φ110*120mm	50000 hrs	-30°~40°C
DLO-15-IR	220-240V /AC	CREE COB	15W	1360 lm	2700K-5000K	φ110*120mm	50000 hrs	-30°~40° C
DLO-20-IR	220-240V /AC	CREE COB	20W	1900 lm	2700K-5000K	φ130*153mm	50000 hrs	-30°~40°C
DLO-25-IR	220-240V /AC	CREE COB	25W	2300 lm	2700K-5000K	φ130*153mm	50000 hrs	-30°~40°C
DLO-35-IR	220-240V /AC	CREE COB	35W	3000 lm	2700K-5000K	φ170*183mm	50000 hrs	-30°~40°C
DLO-40-IR	220-240V /AC	CREE COB	40W	3400 lm	2700K-5000K	φ195*193mm	50000 hrs	-30°~40°C
DLO-50-IR	220-240V /AC	CREE COB	50W	4300 lm	2700K-5000K	φ195*193mm	50000 hrs	-30°~40° C