

Surface Mounted Waterproof Cylinder Downlight

Britlite DLOWP-Orion Series a superior surface mounted Cylinder Downlight in IP65 option for variety of exterior building lighting applications.

Constructed from a die-cast and extruded aluminium body, the Downlight is available in black or white, and five colour reflector options to perfectly suit the aesthetics of your project.

A sleek & elegant design with a stack-effect heat sink which is sufficient for cooling & ensuring the long lifespan of the light.



Application:

- Villa, Lobbies, Corridors
- Hotel Lighting Restaurant
- Residential Lighting



golden



silver



black



White

Surface Mounted Waterproof Cylinder Downlight

Features:

- LED Inside with Anti-glare rings UGR<13
- 5 colors of reflectors optional for different applications
- SDCM=3
- Extremely long lifetime
- Energy savings
- Maintenance savings
- instant light-up
- Excellent light quality
- No UV or IR radiation
- Environmentally-friendly: no mercury
- Medium useful life > 50,000 hours (L80B50) at ambient temperature of 25 °C

Specification:

- Power supply : Eaglerise
- Lighting Source: Original Philips (90Ra+) CREE (90Ra+)
- Housing material: aluminum.
- Housing color: White Black
- Working environment temperature: -20°C ~ +45°C
- Lamp Certificates: CE ROHS



IP65

	Electrical parameters			Optical parameters				Physical parameter	
Product Code	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(o)	CCT (K)	CRI	Size (mm)	Ring color
Orion-C-DLO10	AC220-240V AC100-277V	10W	CREE/Philips /Bridgelux	100LM/W	20/40	2700K 3000K 4000K 5000K	80+/90+	D75 H100mm	Silver White Black Goden Nickle
Orion-C-DLO15	AC220-240V AC100-277V	15W	CREE/Philips /Bridgelux	100LM/W	20/40	2700K 3000K 4000K 5000K	80+/90+	D75 H152mm	Silver White Black Goden Nickle
Orion-C-DLO20	AC220-240V AC100-277V	20W	CREE/Philips /Bridgelux	100LM/W	20/40	2700K 3000K 4000K 5000K	80+/90+	D95 H152mm	Silver White Black Goden Nickle
Orion-C-DLO30	AC220-240V AC100-277V	30W	CREE/Philips /Bridgelux	100LM/W	20/40	2700K 3000K 4000K 5000K	80+/90+	D115 H152mm	Silver White Black Goden Nickle
Orion-C-DLO40	AC220-240V AC100-277V	40W	CREE/Philips /Bridgelux	100LM/W	20/40	2700K 3000K 4000K 5000K	80+/90+	D140 H162mm	Silver White Black Goden Nickle
Orion-C-DLO50	AC220-240V AC100-277V	50W	CREE/Philips /Bridgelux	100LM/W	20/40	2700K 3000K 4000K 5000K	80+/90+	D170 H182mm	Silver White Black Goden Nickle
Orion-C-DLO60	AC220-240V AC100-277V	60W	CREE/Philips /Bridgelux	100LM/W	20/40	2700K 3000K 4000K 5000K	80+/90+	D205 H212mm	Silver White Black Goden Nickle

Surface Mounted Waterproof Cylinder Downlight

Pictures

