

# CYCLONE-II

## SMD LED DOWNLIGHT

BRITLITE Cyclone-II LED recessed downlight is a cost effective and well performing downlight solution to the market, it comes with an anti-glare PMMA Cover, opal diffuser, complete with high quality LED Driver, with a wide unique sunken design to protect your eyes from glare, a comfortable and a very homogenous light



### Application:

- General Lighting Areas
- Hotel & Office Lighting
- Residential Lighting
- Retail Shops



# CYCLONE-II

## SMD LED DOWNLIGHT

### Features:

- Opal diffuser glare free design, No flickers.
- Direct replacement for compact fluorescent lamp downlights
- Energy savings of up to 60 % compared to luminaires that use CFL
- Adopt aluminum alloy as material die-casting process.
- Low UGR < 19
- High transmission PMMA Cover
- No UV or IR radiation
- Medium useful life > 50,000 hours (L80B50) at ambient temperature of 25° C
- Working environment temperature: -20°C ~+45°C
- Dimming options : Triac 0/ 1-10V DALI
- Lamp Certificates: CE ROHS SAA



Product Code	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(o)	CCT (K)	CRI	Size (mm)	Cutout(mm)
BL-DLP15W	AC220V-240V	15W	OSRAM	1500LM	70°	2700K 3000K 4000K 5000K 6000K	80+	Φ138*68mm	ø115-120mm
BL-DLP20W	AC220V-240V	20W	OSRAM	2000LM	70°	2700K 3000K 4000K 5000K 6000K	80+	Φ185*83mm	ø150-170mm

