

GALAXY-II

Anti-glare Recessed Mounted Downlight

Britlite Galaxy-II Series LED Downlight is designed with a shielded light source with precise cut off reflectors that reduces glare, accurate beam angle, perfect light control, deep hidden anti glare design, creating an excellent lighting environment.

It is Ideal for your planned retrofit creating tremendous energy saving at a extremely affordable price.



Application:

- Villa, Lobbies, Corridors, Malls
- Hotels, Restaurants, Hospitals
- Residential Lighting



golden



silver



black



White

GALAXY-II

Anti-glare Recessed Mounted Downlight

Information:

Features:

- LED Inside with Anti-glare rings UGR<16
- Various colors of reflectors optional for different application
- SDCM=3
- Long lifetime
- Energy savings
- Maintenance savings
- instant light-up
- Excellent light quality
- No UV or IR radiation
- Environmentally-friendly: no mercury
- Medium useful life > 50,000 hours (L80B50) at ambient temperature of 25 °C



Specification:

- Power supply : Lifud or Philips
- Housing material: aluminum.
- Housing color: White Black
- Working environment temperature: -20°C~ +45°C
- Lamp Certificates: CE ROHS



Product Code	Electrical parameters			Optical parameters				Physical parameter	
	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(°)	CCT (K)	CRI	Size (mm)	Cutout (mm)
BL-DLH- A05W	AC220-240V	5W	BRIDGELUX/CREE	100LM/W	15/24/36°	2700K 3000K 4000K 5000K	80+/90+	Ø63*H63	Ø55mm
BL-DLH-A07W	AC220-240V	7W	BRIDGELUX/CREE	100LM/W	15/24/36°	2700K 3000K 4000K 5000K	80+/90+	Ø85*H76	Ø75mm
BL-DLH-A12W	AC220-240V	12W	BRIDGELUX/CREE	100LM/W	15/24/36°	2700K 3000K 4000K 5000K	80+/90+	Ø85*H93	Ø75mm
BL-DLH-A15W	AC220-240V	15W	BRIDGELUX/CREE	100LM/W	15/24/36°	2700K 3000K 4000K 5000K	80+/90+	Ø85*H93	Ø75mm
BL-DLH-A20W	AC220-240V	20W	BRIDGELUX/CREE	100LM/W	15/24/36°	2700K 3000K 4000K 5000K	80+/90+	Ø105*H99	Ø95mm