

VENUS-II

SMD LED DOWNLIGHT

Description:

BRITLITE Venus-II LED recessed downlight is a cost effective and well performing downlight solution to the market, it comes with an anti-glare PMMA Cover, opal diffuser, complete with high quality LED Driver, with a wide unique sunken design to protect your eyes from glare, a comfortable and a very homogenous light.



Application:

- General Lighting Areas
- Hotel & Office Lighting
- Residential Lighting
- Retail Shops



VENUS-II

SMD LED DOWNLIGHT

Features:

- Opal diffuser glare free design, No flickers.
- Direct replacement for compact fluorescent lamp downlights.
- Energy savings of up to 60 % compared to luminaires that use CFL.
- Adopt aluminum alloy as material die-casting process.
- Low UGR < 19
- High transmission PMMA Cover.
- No UV or IR radiation
- Medium useful life > 50,000 hours (L80B50) at ambient temperature of 25 °C
- Working environment temperature: 20°C ~+45°C
- Dimming options : Triac 0/ 1-10V DALI
- Lamp Certificates: CE ROHS SAA

Product Code	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(o)	CCT (K)	CRI	Size (mm)	Cutout(mm)
BL-DLP9 P5	AC220V-240V	9W	OSRAM	900LM	100	2700K 3000K 4000K 5000K 6000K	80+	Φ115*48mm	ø100-105mm
BL-DLP15 P5	AC220V-240V	15W	OSRAM	1500LM	100	2700K 3000K 4000K 5000K 6000K	80+	Φ145*60mm	ø130-135mm
BL-DLP18 P5	AC220V-240V	18W	OSRAM	1800LM	100	2700K 3000K 4000K 5000K 6000K	80+	Φ159*60mm	ø145-150mm
BL-DLP25 P5	AC220V-240V	25W	OSRAM	2600LM	100	2700K 3000K 4000K 5000K 6000K	80+	Φ190*60mm	ø170-180mm
BL-DLP30 P5	AC220V-240V	30W	OSRAM	3000LM	100	2700K 3000K 4000K 5000K 6000K	80+	Φ230*72mm	ø205-215mm
BL-DLP35 P5	AC220V-240V	35W	OSRAM	3500LM	100	2700K 3000K 4000K 5000K 6000K	80+	Φ230*72mm	ø205-215mm

